

AC Digital Clamp Meter

CM-2100 / CM-2200

HTC
INSTRUMENTS

Features :

- 3¾ Digits LCD Display
- 4000 Counts
- CE CAT III 600V
- Data Hold Function
- Relative Function
- Auto Range Selection
- Max. Jaw Size : 57mm
- AC Current 1500A (CM-2100)
- AC Current 2000A (CM-2200)
- Auto Power Off



Technical Data :

Function	Range	Resolution	Accuracy	Input Impedance
DCV	4 / 40 / 400 / 1000V	1mV	±(1.0% +3d)	10MΩ
ACV	4 / 40 / 400 / 750V	1mV	±(1.5% +5d)	10MΩ
ACA	400 / 1500A (CM-2100)	0.1A	±(2.5% +5d)	
	400 / 2000A (CM-2200)			
Resistance	400 / 4K / 40K / 400K / 4M / 40MΩ	0.1Ω	±(1.0% +3d)	
Frequency	10 / 100 / 1K / 10K / 100K / 1MHz	0.01Hz	±(1.0% +3d)	
Continuity	Buzzer Sound at less than 20Ω			
Diode	Open Voltage : 0.6mA Open Voltage : 1.5V	1mV		

- **Standard Accessories** : Carrying Case, Test Leads, Manual
- **Dimension** : 280(H) x 100(W) x 50(D)mm