

KUSAM-MECO

PHOTO / CONTACT TACHOMETER (Laser)

FEATURES

- **Display** : 5 digits 18 mm(0.6") LCD
- **Accuracy** : $\pm (0.05\% + 1 \text{ digit})$
- **Sampling Time** : 0.5 Sec(over 120RPM)
- **Range Select** : Auto-Ranging
- **Memory** : Last value, Max. Value, Min. value
- **Power Consumption** : Approx 55mA
- **Time Base** : 6 MHz Quartz crystal
- **Detecting Distance** : 50 mm to 500 mm
- **Measuring range** : PHOTO TACH 2.5 TO 99999 RPM CONTACT TACH 0.5 TO 19,999 RPM SURFACE SPEED(m/min) 0.05 TO 1,999.9 (m/ min).
- **Resolution** : PHOTO TACH 0.1 RPM (2.5 to 999.9 RPM) 1 RPM (over 1000 RPM)
CONTACT TACH 0.1 RPM(0.5 to 999.9 RPM) 1RPM (over 1000RPM)
SURFACE SPEED(m/min) 0.01 m/min (0.05 to 99.99 m/min)
0.1 m/min (over 100 m/min)
- **Power** : 4 X 1.5 V AA Size Battery or to external DC 6V Regulated power supply.

MODEL KM 2241



Note: All Specification are Subject to change.

KUSAM-MECO

An ISO 9001:2000 Certified company

Industrial Supply Syndicate

Office : 54. Ezra Street, Kolkata - 700 001, India.

Tel. : (033) 22350923, 22356676 Fax : (033) 3022 2923

E-mail : info@industrialindia.com, Website : www.industrialindia.com