KUSAM-MECO

An ISO 9001:2000 Company

Model - KM 5420





COMBUSTIBLE GAS LEAK DETECTOR

Features :

- * Easy one hand operation.
- * Sensor provides accurate detection.
- Replaceable sensor.
- * Sensitivity thumb-wheel.
- * Visual and audible alarms signal.
- Flash LED indicate leak strength.
- * Long 15" gooseneck for hard to reach areas.
- * Rubber boot protects instrument.
- * Adjustable sensitivity helps pinpoint leaks fast.
- * All types of Combustable Gas Detection.

SPECIFICATIONS :

Weight	Approx. 230g including battery.	
Dimensions	185mm(H) x 65mm(W) x 35mm(D).	
Battery	9V Alkaline or Li-ion Battery.	
Tic Indication	Flashing LED.	
Storage temperature	-20°C to 60°C, 0 to 80% R.H with battery removed from meter.	
Operating environment	0°C to 50°C at <75% R.H.	
Tic Adjustment	Fully adjustable thumbwheel.	
Sensitivity	5 ppm	
Accuracy	Stated accuracy at 23°CiÓ5°C, <75% R.H.	



Industrial Supply Syndicate, 54, Ezra Street, Kolkata - 700 001, India Phone: +91 33 22350923, 22356676 Fax: 30222923 Email: info@industrialindia.com Website: www.industrialindia.com