

**SPECIFICATIONS**

Basic Function	Range	Accuracy
Insulation Resistance	0.5MΩ ~ 1000GΩ (1TΩ)	± (3% + 5)
Testing Voltage	500V/1000V/2500V/5000V	0 ~ 20%
DC Voltage	600V	± (2% + 5)
AC Voltage	600V	± (2% + 5)

**Special Function**

- Auto Ranging
- Short Circuit Current : <1.8mA
- Data Logging : 18 data
- Sleep Mode
- Polarization Index (PI) function.
- Dielectric Absorption Ratio (DAR) Measurement
- Timer : Around 15 minutes
- Compare
- Low Battery indication
- White Display Backlight
- Over Range and High Voltage Warning
- USB port
- Max. Display: 9999
- Analogue Bar Graph & Digital display

**GENERAL SPECIFICATIONS**

- Power : 1.5V Alkaline Battery X 8
- LCD Size : 123 X 58mm
- Product Weight : 2 kg.
- Dimension : 202 x 155 x 94 mm
- Standard Accessories : Two pcs of one plug test lead to one alligator clip (Black & Green), One pc of Two plugs test lead to alligator clip (Red), Batteries, English Manual, Tool Box, USB Interface Cable, Software, Power Adaptor.

Note: All Specification are Subject to change.

**MODEL - KM 2805**

Preliminary Data