

KUSAM-MECO

3 1/2 DIGIT (2000 COUNTS)


MODEL NO. 2718

DIGITAL DC/AC

CLAMP METER



FEATURES

- **Jaws Opening Capability** : 32mm
- **Measuring method** : Dual-slope integration A/D Converter system
- **Over-range indication** : Figure "1" or sing "OL"
- **Over load protection** : protected by PTC in the resistance range
- **DATA HOLD function** : The hold and release for All display data is performed alternatively By "D.H" push switch.
- **Low Battery Indication** : The "  " symbol is displayed when the battery voltage drops below accurate operating level.
- **Operating Temperature** : 0°C to 50°C
Relative Humidity : 80% max.
- **Storage Temperature** : -20°C to 60°C
Relative Humidity : 80% max.
- **Dimension** : 205mm(L) x 71mm(W) x 38.8mm(H)
- **Weight** : Approx. 272gms.
- **Power** : 9V Alkaline or carbon-zinc battery.
- **Accessories** : Test Leads, Carrying Case, Temp. Probe, Instruction Manual

TECHNICAL SPECIFICATIONS:

AC CURRENT

Range	Resolution	Accuracy
200 A	0.1 A	± (1.5% rdg + 4 dgts)
600 A		

AC VOLTAGE

Range	Resolution	Accuracy
600 V	1 V	± (1.5% rdg + 4 dgts)

DC VOLTAGE

Range	Resolution	Accuracy
600 V	1 V	± (1.0% rdg + 2 dgts)

RESISTANCE

Range	Resolution	Accuracy
200	0.1	± (1.0% rdg + 2 dgts)
2000	1	
400	0.1	± (1.0% rdg + 4 dgts)
40 M		

FREQUENCY

Range	Resolution	Accuracy
0-10 MHz	0.001 Hz	± (0.8% rdg + 2 dgts)

CAPACITANCE

Range	Resolution	Accuracy
40 nf	0.01 nf	± (2.5% rdg + 2 dgts)
100 uf		

TEMPERATURE

Range	Resolution	Accuracy
-40°C	1 °C	± (3% rdg + 4 dgts)
1000°C		

KUSAM-MECO
AN ISO 9001:2000 COMPANY

Industrial Supply Syndicate

54, Ezra Street, Kolkata -700 001. Phone: 3291 6080, 2235 6676 Fax: 033 3022 2923
E-mail : info@industrialindia.com, Website : www.industrialindia.com