



An ISO 9001:2000 Company

WATERPROOF PH, ORP, CONDUCTIVITY TDS, EC PEN TESTER

MODEL - 6011, 6011A, 6021, 6022, 6031, 6032, 6061



MODEL
6011/6011A



MODEL
6021



MODEL
6022



MODEL
6031



MODEL
6032



MODEL
6061

SPECIAL FEATURES :

- Fast response, reliable and accurate measurements.
- Large LCD display 21 x 18mm for easy reading.
- Impact resistant ABS case by waterproof designed IP 57 rated.
- 1 or 2 points (pH only) manual calibration via screw trim pot.
- The electrode module are changeable for replacement by user.

ACCESSORIES :

Standard solution, Battery, Screwdriver, Carrying case & instruction Manual.

ELECTRICAL SPECIFICATIONS

Models Functions	6011	6011A	6021	6022	6031	6032	6061
Type	pH	pH	Conductivity	Conductivity	TDS	TDS	EC
Range	0~14.0	0~14.00	0~19990mS	0~1999mS	0~19990 ppm	0~1999 ppm	0~19.99 EC
Accuracy	± 0.1+1 digit	± 0.1+1 digit	± 1% FS	± 1% FS	± 1% FS	± 1% FS	± 1% FS
Resolution	0.1 pH	0.01 pH	10 mS/cm	1 mS/cm	10 ppm	1 ppm	0.01 EC
ATC *	No	No	Yes	Yes	Yes	Yes	Yes
Power	3V x 2 Lithium battery	3V x 2 Lithium battery	3V x 2 Lithium battery	3V x 2 Lithium battery	3V x 2 Lithium battery	3V x 2 Lithium battery	3V x 2 Lithium battery
Dimension	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm	33.5 x 170 mm
Weight	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)	Approx. 85g. (Including battery)

*Automatic Temperature Compensation

All specifications are subject to change without prior notice.



An ISO 9001:2000 Company

Industrial Supply Syndicate

54, Ezra Street, Kolkata - 700 001, INDIA

Phone: 22350923, 22356676 Fax: +91 33 30222923

Email: info@industrialindia.com Website: www.industrialindia.com