

**KUSAM-MECO**

An ISO 9001:2008 Company



# DIGITAL COATING THICKNESS GAUGE FOR FERROUS BASE MATERIAL MODEL KM 117A

## INTRODUCTION :

KM 117A is a portable, easy to use digital coating thickness gauge designed for simple one hand operation.

Meter comes with Back-light LCD display,  $\mu\text{m}/\text{mils}$  user-selective and Auto Power Off (30 seconds approx.) function.

## FEATURES :

- Measures coating thickness on Ferrous base materials.
- Portability and simple one hand operation.
- Select the on-line display for one off MAX/MIN/MAX-MIN/AVG function.
- Fast one point calibration for frequent measuring thickness use.
- 2-point calibration for normal use.
- Auto-power off.
- LED Back-light & LCD display Reverse for easy reading.
- Data logging function capacity up to 255 samples.
- Warning beeper triggers by Hi/Lo limit settings.
- $\mu\text{m}/\text{mils}$  user-selective.
- Inch & Metric measurement options.
- Zeroing Plate & Standard Coating Plate.
- Attached with carrying strap.



Preliminary Data

## GENERAL SPECIFICATIONS :

\* **Detectable Substrate Material** : Ferrous metal (iron, steel).

\* **Thickness Range** : 0 ~ 80.0mils (0 ~ 2000 $\mu\text{m}$ ).

\* **Display Resolution** : 0.1mils/1 $\mu\text{m}$ .

### \* **ACCURACY :**

**KM 117A Ferrous :**

$\pm 4$ dgts on 0 to 7.8mils

$\pm(3\%+4$ dgts) on 7.9mils to 39.0mils

$\pm(5\%+4$ dgts) on 39.1mils to 80mils

$\pm 10$ dgts on 0 to 199 $\mu\text{m}$

$\pm(3\%+10$ dgts) on 200 $\mu\text{m}$  to 1000 $\mu\text{m}$

$\pm(5\%+4$ dgts) on 1001 $\mu\text{m}$  to 1999 $\mu\text{m}$

**Response Time** : 1 second

\* **Operating Environment** : 0°C to 50°C (32°F to 122°F) at < 75% RH

\* **Relative Humidity** : Maximum relative humidity 80% for temperature up to 60°C decreasing linearly to 75% relative humidity at 50°C

\* **Storage Temperature** : -20°C ~ 60°C (-4°F to 140°F), <80% R.H. (with battery removed)

\* **Temperature Coefficient** : Nominal 0.1 x (specified accuracy) / °C @ (<18°C or >28°C)

\* **Stand by Consuming Current** : < 6 $\mu\text{A}$

\* **Power Supply** : Standard 1.5V AAA Size Battery X 2

\* **Dimension** : 105(H) x 55(W) x 27(D)mm

\* **Weight** : approx 80 g (including battery).

## ACCESSORIES :

Users Manual, Battery & carrying case.

All Specifications are subject to change without prior notice

**KUSAM-MECO**

An ISO 9001:2008 Company

## Industrial Supply Syndicate

54, Ezra Street, Kolkata - 700 001, India

Phone: (033) 22350923, 22356676 Fax: (91-33) 3022 2923

Email: info@industrialindia.com Website: www.industrialindia.com